

Model Name	POS 335
Motherboard	C56
Processor	Intel Cedarview D2550 Dual Core 1.86G, L2 1M, 10W
Chipset	CPU integrated graphic + NM10, 2W
System Memory	1 x DDR3 SO-DIMM, 2GB, 1066MHz
Graphic Memory	Intel GMA 3650 (Gfx frequency up to 640MHz), DX9
LCD / Touch Panel	
LCD Size	15" TFT LCD
Brightness	250 cd/m ²
Resolution	1024x768
Touch Screen	Resistive
Tilt Adjustment	4° ~ 84°
Storage Device	
Hard Drive	one 2.5" SATA HDD bay
Flash Memory	SSD 32Gb
Expansion	
miniPCI-E Slot	1
External I/O Ports	
USB 2.0	6
Serial Port	4 x RJ45 COM ports (COM1 standard RS232; COM2/3/4 powered RS232; COM2 default 0V; COM3 default 5V; COM4 default 12V, power enabled by BIOS)
Parallel Port	1 (option, 1 Parallel and 4 USB instead of 6 USB)
Giga LAN (10/100/1000)	1 (RJ45)
VGA	1 (12V power enabled by BIOS)
Cash Drawer	1 (RJ11)
DC Jack	1
Power	
Power Supply	65W/19V
Control / Indicator	
Power Button	1
Indicator LED	1
Peripheral (option)	
MSR	MSR (USB)
Finger print	1 (USB) instead of MSR
Second display	8.4" (4:3) without touch
Customer display	VFD display 2 x 20 characters (COM)
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	



Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Humidity	20% ~ 85% RH non-condensing
Communication	
Wireless LAN	802.11 b/g/n wireless LAN card & antenna (Option)
Dimensions (WxDxH)	LCD 4° tilt angle: 365 x 296 x 282 mm (14.4" x 11.7" x 11.1") LCD 84° tilt angle: 365 x 218 x 343 mm (14.4" x 8.6" x 13.5")
Weight	5.8kg (12.8lbs)
Mouning	100 x 100 mm standard VESA holes
OS Supported	Windows XP, POS Ready 2009, XP Embedded, XP professional for Embedded, Linux, Windows 7 (32bit), POSReady 7(32bit)