

12.1", 15", 17" Touch Monitor

Features

- Resistive touch monitor
- Spill proof & anti dust
- Smart cable management
- Wall-mount supporting
- Support 2nd display & MSR



OT12



OT15



OT17



Specifications

Model	OT12TA/		OT12TB		OT15TA		OT15TB		OT17TA		OT17TB	
Display size	12.1"				15"				17"			
Display Area	246 * 184 mm				304 * 228 mm				338 * 270 mm			
Optimal Resolution	1024 X 768				1024 X 768				1280 X 1024			
Panel Brightness	500 cd/m ² (typ)				250 cd/m ² (typ)				250 cd/m ² (typ)			
Contrast Ratio	700 : 1				600 : 1				1000 : 1			
Response Time	26 ms (typ)				8 ms (typ)				5 ms (typ)			
Viewing Angle	160 degrees (H)				160 degrees (H)				170 degrees (H)			
	140 degrees (V)				160 degrees (V)				160 degrees (V)			
Input Video signal	D-Sub 15 pins		D-Sub 15 pins+DVHD		D-Sub 15 pins		D-Sub 15 pins+DVHD		D-Sub 15 pins		D-Sub 15 pins+DVHD	
Power consumption	10W				20W				30W			
Input Frequency	Horizontal : 31.5 kHz~60.2 kHz Vertical : 56.3Hz~75Hz											
Power supply	DC 12V +/- 10%											
Temperature	Operating : 0°C~40°C						Storage : -10°C~50°C					
Humidity	Operating : 20%~80%						Storage : 10%~90%					
Weight	4.5Kg(net)				4.67Kg(net)				5.86Kg(net)			
Wall Mount	VESA 75 * 75 mm						VESA 100 * 100 mm					
Optional	VFD 2X20, 2nd Display (OT07, OT84) , MSR, Wall Mount Bracket											

This specification is subject to change without prior notice.